

Appl. No. 10/045,290
Amdt. dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (previously presented) A method of inserting empty memory cells into a data flow of network connections of a computer network, the method comprising:
receiving an insertion request for an empty memory cell to be inserted into the data flow;
determining an appropriate insertion scheme for carrying out the insertion request, wherein the appropriate insertion scheme includes a first insertion scheme configured to send the insertion request using a first indicator that the empty memory cell should be shaped using predetermined shaping parameters and a second insertion scheme configured to send the insertion request using a second indicator that the empty memory cell should be unshaped; and
sending the insertion request to an insertion device configured to insert the empty memory cell into a main buffer for the data flow, the insertion request including the first indicator or the second indicator based on the appropriate insertion scheme determined.
2. (previously presented) The method of Claim 1, further comprising receiving a base connection identification (CID) associated with the insertion request, wherein the first insertion scheme is configured to send the insertion request using the base connection identification (CID), wherein the base connection identification is associated with predetermined shaping parameters.
3. (previously presented) The method of Claim 2, wherein the method further comprises shaping the empty memory cell according to the predetermined shaping parameters.

Appl. No. 10/045,290
Amdt. dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

4. (previously presented) The method of Claim 1, wherein the second insertion scheme is configured to send the insertion request using dedicated unshaped connection identifications.

5. (previously presented) The method of Claim 4, wherein there are 16 unshaped connection identifications.

6. (previously presented) The method of Claim 4, the method further comprising:

configuring the dedicated unshaped connection identifications for the computer network to obtain configured connection identifications;

configuring the base connection identification for the configured connection identifications;

configuring a cell type indication to be used for the insertion request; and

configuring a queue identification to be used for the insertion request.

7. (previously presented) The method of Claim 1, wherein the insertion request is received from one of:

an operations and maintenance (OAM) device;

a performance monitoring device;

an available bit rate (ABR) device;

a central processing unit; or

an operations and maintenance scan device.

8. (previously presented) The method of Claim 7, wherein the performance monitoring device and the operations and maintenance scan device each requires the insertion request to be carried out with the first insertion scheme.

Appl. No. 10/045,290
Amdt. dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

9. (previously presented) The method of Claim 1, wherein the an available bit rate (ABR) device requires the insertion request to be carried out with the second insertion scheme.

10. (previously presented) The method of Claim 1, wherein the step of determining the appropriate insertion scheme comprises performing a lookup in a scan table.

11. (previously presented) The method of Claim 1, wherein the step of sending the insertion request causes the empty memory cell to be transmitted through the data flow.

12. (previously presented) The method of Claim 6, wherein the empty memory cell inserted by the insertion device carries the cell type indication.

13. (previously presented) An integrated circuit configured to insert empty memory cells into a data flow of network connections of a computer network, the integrated circuit comprising:

controller circuitry configured to control operations of:

receiving an insertion request for an empty memory cell to be inserted into the data flow;

determining an appropriate insertion scheme for carrying out the insertion request, wherein the appropriate insertion scheme includes a first insertion scheme configured to send the insertion request using a first indicator that the empty memory cell should be shaped using predetermined shaping parameters and a second insertion scheme configured to send the insertion request using a second indicator that the empty memory cell should be unshaped; and

based on the appropriate insertion scheme, sending the insertion request to an insertion device configured to insert the empty memory cell into a main buffer for the data flow, the insertion request including the first indicator or the second indicator based on the appropriate insertion scheme determined.

Appl. No. 10/045,290
Amdt. dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

14. (previously presented) The integrated circuit of Claim 13, further comprising receiving a base connection identification (CID) associated with the insertion request, wherein the first insertion scheme is configured to send the insertion request using the base connection identification (CID), wherein the base connection identification is associated with predetermined shaping parameters.

15. (previously presented) The integrated circuit of Claim 14, wherein the controller circuitry is further configured to control shaping the empty memory cell according to the predetermined shaping parameters.

16. (previously presented) The integrated circuit of Claim 13, wherein the second insertion scheme is configured to send the insertion request using dedicated unshaped connection identifications.

17. (previously presented) The integrated circuit of Claim 16, wherein there are 16 unshaped connection identifications.

18. (previously presented) The integrated circuit of Claim 16, wherein the controller circuitry is further configured to control operations of:

configuring the dedicated unshaped connection identifications for the computer network to obtain configured connection identifications;

configuring the base connection identification for the configured connection identifications;

configuring a cell type indication to be used for the insertion request; and

configuring a queue identification to be used for the insertion request.

19. (previously presented) The integrated circuit of Claim 13, wherein the insertion request is received from one of:

an operations and maintenance (OAM) device;

a performance monitoring device;

Appl. No. 10/045,290
Amdt. dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

an available bit rate (ABR) device;
a central processing unit; or
an operations and maintenance scan device.

20. (previously presented) The integrated circuit of Claim 19, wherein the performance monitoring device and the operations and maintenance scan device each requires the insertion request to be carried out with the first insertion scheme.

21. (previously presented) The integrated circuit of Claim 13, wherein the an available bit rate (ABR) device requires an insertion request to be carried out with the second insertion scheme.

22. (previously presented) The integrated circuit of Claim 13, wherein with the step of determining an appropriate insertion scheme, the controller circuitry is further configured to control performing a lookup in a scan table.

23. (previously presented) The integrated circuit of Claim 13, wherein the step of sending the insertion request causes the empty memory cell to be transmitted through the data flow.

24. (previously presented) The integrated circuit of Claim 18, wherein the empty memory cell inserted by the insertion device carries the cell type indication.

25. (previously presented) A computer-readable medium carrying one or more sequences of one or more instructions for inserting empty memory cells into a data flow of network connections of a computer network, the one or more sequences of one or more instructions including instructions which, when executed by one or more processors, cause the one or more processors to perform steps of:

receiving an insertion request for an empty memory cell to be inserted into the data flow;

Appl. No. 10/045,290
Amdt, dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

determining an appropriate insertion scheme for carrying out the insertion request , wherein the appropriate insertion scheme includes a first insertion scheme configured to send the insertion request using a first indicator that the empty memory cell should be shaped using predetermined shaping parameters and a second insertion scheme configured to send the insertion request using a second indicator that the empty memory cell should be unshaped; and based on the appropriate insertion scheme, sending the insertion request to an insertion device configured to insert the empty memory cell into a main buffer for the data flow , the insertion request including the first indicator or the second indicator based on the appropriate insertion scheme determined.

26. (previously presented) The computer-readable medium of Claim 25, further comprising receiving a base connection identification (CID) associated with the insertion request, wherein the first insertion scheme is configured to send the insertion request using the base connection identification (CID), wherein the base connection identification is associated with predetermined shaping parameters.

27. (previously presented) The computer-readable medium of Claim 26, wherein the instructions further cause the processor to perform a step of shaping the empty memory cell according to the predetermined shaping parameters.

28. (previously presented) The computer readable-medium of Claim 25, wherein the second insertion scheme is a predetermined insertion scheme configured to send the insertion request using dedicated unshaped connection identifications.

29. (previously presented) The computer-readable medium of Claim 28, wherein there are 16 unshaped connection identifications.

30. (previously presented) The computer-readable medium of Claim 28, wherein the instructions further cause the processor to perform steps of:

Appl. No. 10/045,290
Amdt. dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

configuring the dedicated unshaped connection identifications for the computer network to obtain configured connection identifications;

configuring the base connection identification for the configured connection identifications;

configuring a cell type indication to be used for the insertion request; and

configuring a queue identification to be used for the insertion request.

31. (previously presented) The computer-readable medium of Claim 25, wherein the insertion request is received from one of:

an operations and maintenance (OAM) device; a performance monitoring device;

an available bit rate (ABR) device; a central processing unit; or

an operations and maintenance scan device.

32. (previously presented) The computer-readable medium of Claim 31, wherein the performance monitoring device and the operations and maintenance scan device each requires the insertion request to be carried out with the first insertion scheme.

33. (previously presented) The computer-readable medium of Claim 25, wherein the an available bit rate (ABR) device requires the insertion request to be carried out with the second insertion scheme.

34. (previously presented) The computer-readable medium of Claim 25, wherein the step of determining the appropriate insertion scheme further causes the processor to perform a lookup in a scan table.

35. (previously presented) The computer-readable medium of Claim 25, wherein the step of sending the insertion request causes the processor to perform a step of transmitting the empty memory cell through the data flow.

36. (previously presented) The computer-readable medium of Claim 30, wherein the empty memory cell inserted by the insertion device carries the cell type indication.

Appl. No. 10/045,290
Amdt. dated February 28, 2006
Amendment under 37 CFR 1.116 Expedited Procedure
Examining Group 2666

PATENT

37. (previously presented) A device of inserting empty memory slots into a data flow, the device comprising:

logic configured to receive an insertion request for an empty memory slot to be inserted into the data flow;

logic configured to determine an appropriate insertion scheme for carrying out the insertion request, wherein the appropriate insertion scheme includes a first insertion scheme configured to send the insertion request using predetermined shaping parameters, wherein connection identification is associated with predetermined shaping parameters and a second insertion scheme configured to send the insertion request using an unshaped connection identification; and

logic configured to send the insertion request to an insertion device configured to insert the empty memory slot into the data flow, wherein the insertion of the empty memory slot into the data flow is performed before shaping of the data flow.